



Trusted Aerosol Performance

## SAFETY DATA SHEET

### Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** Dry Lube PTFE Aerosol FG84 (Food Grade) 400ml  
**Product Code:** 7284  
**Uses:** Dry Film PTFE Lubricant  
**Company:** Chemz Limited  
**Address:** 80 Rangitane Place  
Whakatu, Hastings  
**Telephone:** +64 6 877 9690  
**Email:** info@chemz.co.nz  
**Emergency Number 24 hr:** 0800 764 766 (0800 POISON) National Poison Centre

### Section 2 – HAZARDS IDENTIFICATION

#### Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.  
Classified as a dangerous goods for transport purposes.

#### GHS Classifications:

Aerosol Category 1  
Eye irritation Category 2

#### HSNO Classifications:

2.12A Flammable Aerosol  
6.4A Irritating to the eye



**Signal Words:** Danger

#### Hazard Statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 May cause serious eye irritation.

### Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
2-Propanol	67-63-0	10 - 30
Polytetrafluoroethylene (PTFE)	65530-85-0	1 - 10
Hydrocarbon propellant (LPG - Propane, Butane)	124-38-9	> 60

### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

**Eye contact:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention



Trusted Aerosol Performance

## SAFETY DATA SHEET

<b>Skin contact:</b>	IF ON SKIN: Wash with plenty of soap and water. Direct contact may cause irritation in sensitive individuals. If skin irritation occurs: Get medical advice/ attention.
<b>Inhalation:</b>	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
<b>Ingestion:</b>	Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention
<b>Notes to physician:</b>	Treat symptomatically and supportively. No specific antidote.

### Section 5 – FIRE-FIGHTING MEASURES

<b>General fire hazards:</b>	Pressurised, extremely flammable aerosol.
<b>Specific hazards:</b>	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re-ignited on surface water. Will burn if involved in a fire.
<b>Further advice:</b>	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
<b>Extinguishing media:</b>	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.  For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment.  Do NOT use straight streams of water.
<b>Protective equipment:</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Firefighting instructions:</b>	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
<b>Hazchem Code:</b>	2YE

### Section 6 – ACCIDENTAL RELEASE MEASURES

<b>Minor spills:</b>	Clean up all spills immediately. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.
<b>Major spills:</b>	Evacuate the spill area. Call the Fire Brigade. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

### Section 7 – HANDLING AND STORAGE

<b>Handling Precautions:</b>	Read product label before use. Keep out of reach of children.  This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.  Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.  Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.
<b>Storage:</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat and flame. Store locked up.

### Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Exposure Limits:</b>	No value assigned for product. Exposure standards for constituents (NZ WES);
-------------------------	--



Trusted Aerosol Performance

## SAFETY DATA SHEET

Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
2-Propanol	983	1230
LPG (Liquefied petroleum gas – butane, propane)	1800	-

<b>Additional Information:</b>	Wash hands before eating, drinking and smoking.
<b>Engineering Controls:</b>	No controls generally required when handling small quantities. Use with adequate ventilation.  Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion-resistant.
<b>Protective Equipment:</b>	General protective gloves are recommended. In an industrial environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.  In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Colourless spray with characteristic odour, dries to a white film.
<b>pH:</b>	Not applicable.
<b>Vapour Density:</b>	> 1 (Air =1)
<b>Vapour Pressure, kPa:</b>	300 - 600
<b>Boiling Point, °C:</b>	About 80
<b>Melting Point, °C:</b>	Not applicable.
<b>Specific Gravity:</b>	About 0.78
<b>Flash Point, °C:</b>	< 0 (propellant)
<b>Explosion Limit, % v/v:</b>	LEL 1.2% UEL 9.5%
<b>Autoignition Temp, °C:</b>	Not applicable.
<b>Solubility:</b>	Partially miscible in water.

### Section 10 – STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.
-------------------	--

### Section 11 – TOXICOLOGICAL INFORMATION

<b>Basis for Assessment:</b>	Information given is based on product testing, and/or similar products, and/or components.
<b>Acute Oral Toxicity:</b>	LD <sub>50</sub> calculated to be 5,000 mg/kg (based on component mixture, excluding propellant).
<b>Acute Dermal Toxicity:</b>	LD <sub>50</sub> calculated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
<b>Acute Inhalation Toxicity:</b>	LC <sub>50</sub> estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).  Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
<b>Skin Irritation:</b>	May cause mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
<b>Eye Irritation:</b>	May cause serious eye irritation. Avoid contact with eyes. Moderate inflammation may be expected with redness. Expected to be reversible in less than 7 days.
<b>Inhalation:</b>	May cause drowsiness or dizziness. May act as a simple asphyxiant.
<b>Respiratory Irritation:</b>	Inhalation of vapours or mists may cause irritation to the respiratory system.



Trusted Aerosol Performance

## SAFETY DATA SHEET

<b>Sensitisation:</b>	Not expected to be a contact or respiratory sensitiser.
<b>Mutagenicity:</b>	Not expected to be mutagenic.
<b>Carcinogenicity:</b>	Components in this product are not suspected of causing cancer in humans.
<b>Reproductive toxicity:</b>	Not expected to be a human reproductive toxicant.
<b>Effects on or via lactation:</b>	Not expected to be toxic effects on or via lactation.
<b>Specific Target Organ Toxicity:</b>	Not expected to be harmful to human target organs or systems.
<b>STOT (Narcotic):</b>	Prolonged inhalation of vapours may cause dizziness.
<b>Repeated Dose Toxicity:</b>	Repeated, prolonged exposure by inhalation may cause damage to organs.
<b>Additional Information:</b>	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

### Section 12 – ECOTOXICITY INFORMATION

<b>Ecotoxicity:</b>	Not expected to be ecotoxic
<b>Mobility:</b>	Product is volatile and will rapidly evaporate to the air if released into water.
<b>Persistence/degradability:</b>	More volatile components expected to degrade in air. Low persistence, expected to rapidly degrade in environment.
<b>Bioaccumulation Potential:</b>	Not expected to be bioaccumulative.

### Section 13 – DISPOSAL CONSIDERATIONS

<b>Material Disposal:</b>	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.  Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
<b>Container Disposal:</b>	Recycle empty container if possible or dispose in landfill. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.

### Section 14 – TRANSPORT INFORMATION

<b>Transport:</b>	Classified as a Dangerous Good for transport purposes.  Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
<b>Proper Shipping Name:</b>	Aerosols
<b>UN Number:</b>	1950
<b>Dangerous Goods Class:</b>	2.1
<b>Transport Labels Required:</b>	Class 2.1 Flammable (Land, Sea, Air)



<b>Subsidiary Risk:</b>	Not applicable
<b>Packing Group:</b>	Not applicable
<b>Marine Pollutant:</b>	No
<b>EMS Number</b>	F-D, S-U (UN 1950 Aerosols)



Trusted Aerosol Performance

## SAFETY DATA SHEET

**DG Segregation:** This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

### Section 15 – REGULATORY INFORMATION

**Inventory Listing** NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

**SDS regulations** This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017 (Consolidated 30 September 2022).

**EPA Approval Number:** HSR002515 Aerosols (Flammable) Group Standard 2020.

**EPA Hsno Controls:** Refer to [www.epa.govt.nz](http://www.epa.govt.nz) for information on Controls.  
This substance is to be managed using the conditions specified in an applicable Group Standard.

### Section 16 – OTHER INFORMATION

**Additional information** Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	CAS	Chemical Abstract Service number
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods
	EPA	Environmental Protection Agency
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	IATA	International Air Transport Association
	IMDG	International Maritime Dangerous Goods
	LC <sub>50</sub>	Lethal Concentration, 50% / Median Lethal Concentration
	LD <sub>50</sub>	Lethal Dose, 50% / Median Lethal Dose
	LEL	Lower Explosion Limit
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	NZIOC	New Zealand Inventory of Chemicals
	N.O.S.	Not otherwise specified
	OEL	Occupational Exposure Limit
	PEL	Permissible Exposure Limit
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
	UEL	Upper Explosion Limit

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Chemz Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. If clarification or further information is needed, the user should contact their Chemz representative or Chemz Limited at the contact details on page 1. Chemz Limited's responsibility for the material as sold is subject to the terms and conditions of sale.

End of sds.