



## Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	FG15 Contaminant Release Spray Aerosol
Product Code:	7215
Uses:	Precision electrical and mechanical cleaner
Company:	Chemz Limited
Address:	80 Rangitane Place
	Whakatu, Hastings
Telephone:	+64 6 877 9690
Email:	info@chemz.co.nz
Emergency Number 24 hr:	0800 764 766 (0800 POISON) National Poison Centre

## Section 2 – HAZARDS IDENTIFICATION

### Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

#### **HSNO Classifications:**

2.1.2A	Flammable aerosol
6.3A	Irritating to the skin
6.4A	Irritating to the eye
6.9B (Narcotic)	Harmful to human target organs or systems
9.1B	Ecotoxic in the aquatic environment



Signal Words: Danger

#### **Hazard Statements**

H222	Extremely flammable aerosol
H315	Causes skin irritation
H319	Causes eye irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effect

## Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Naphtha (Petroleum), Hydrotreated Light	64741-66-8	> 60
2-Propanol	67-63-0	< 10
Carbon Dioxide (propellant)	124-38-9	< 10

### **GHS Classifications:**

Flammable aerosol	Category 1
Skin irritation	Category 2
Eye irritation	Category 2B
STOT (single exposure)	Category 3
Aquatic toxicity (acute)	Category 2





NEW ZEALAND MADE FOR THE TRADE

## SAFETY DATA SHEET

#### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

#### notes to physician. Theat symptomatically and supportively. No s

#### Section 5 – FIRE-FIGHTING MEASURES General fire hazards: Pressurised container, extremely flammable aerosol. Specific hazards: Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and be re-ignited on surface water. Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion. **Extinguishing media:** For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water. Protective equipment: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Fire fighting instructions: In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage. Hazchem Code: 2YE

#### Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills:	Clean up all spills immediately. Spills will be extremely slippery. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

Section 7 – HANDLING AND STORAGE

Handling Precautions: Read product label before use. Keep out of reach of children.	
	This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.
	Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.





Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

## Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** 

No value assigned for product. Exposure standards for constituents (NZ WES);

	Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
	Naphtha (Petroleum), Hydrotreated Light	1,400	-
	2-Propanol	983	1,230
	Carbon Dioxide	9,000	54,000
Additional Information:	Wash hands before eating, drinking and smoking.		
Engineering Controls:	No controls required when handling small quantities. Use with adequate ventilation.		
	Larger quantities: General exhaust is adequate under r equipment and lighting should be explosion-resistant.	ormal operating conditions	. Ventilation
Protective Equipment:	Generally not required for small quantities. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.		
	In case of inadequate ventilation wear respiratory prot respiratory prot respirator with a type A filter.	ection. If TWA is exceeded,	wear an approved

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear, liquid spray.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	300 - 600
Boiling Point, °C:	About 95
Melting Point, °C:	Not applicable.
Specific Gravity:	About 0.7
Flash Point, °C:	< 0 (propellant)
Explosion Limit, % v/v:	LEL 1.2% UEL 9.5%
Autoignition Temp, °C:	443
Solubility:	Miscible in water.

## Section 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION		
Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.	
Acute Oral Toxicity:	$LD_{50}$ estimated to be> 5,000 mg/kg (based on component mixture, excluding propellant).	
Acute Dermal Toxicity:	$LD_{50}$ estimated to be > 2,000 mg/kg (based on component mixture, excluding propellant).	
Acute Inhalation Toxicity:	$LC_{50}$ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture). Inhalation of vapours may cause drowsiness (narcotic) and dizziness.	
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.	





Skin Irritation:	Prolonged/repeated contact may cause defatting of the skin and dermatitis.
Eye Irritation:	Spray is irritating to the eye. Expected to be reversible in 7 - 21 days.
<b>Respiratory Irritation:</b>	Inhalation of vapours or mists may cause irritation to the respiratory system.
Sensitisation:	Not expected to be a sensitiser.
Repeated Dose Toxicity:	Prolonged contact with product may result in irritant contact dermatitis.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

## Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity:	Ecotoxic in the aquatic environment.		
Mobility:	Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.		
Persistence/degradability:	Inherently biodegradable.		
<b>Bioaccumulation Potential:</b>	Bioaccumulation is unlikely.		
Section 13 – DISPOSAL CO	NSIDERATIONS		
Material Disposal:	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.		
	Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.		
Container Disposal:	Recycle empty container if possible. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.		
Section 14 – TRANSPORT I	INFORMATION		

Transport:	Classified as a Dangerous Good for transport purposes.		
	Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.		
Proper Shipping Name:	Aerosols		
UN Number:	1950		
Dangerous Goods Class:	2.1		
Transport Labels Required:	Class 2 Flammable (Land, Sea and Air), EHSM (Sea and Air)		
	Land, Sea, Air Sea, Air		



Subsidiary Risk:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	Yes
EMS Number	F-D, S-U (UN 1950 Flammable aerosols)
DG Segregation:	This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.





#### Section 15 – REGULATORY INFORMATION

Inventory Listing	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.	
SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.	
Approved Handler:	2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).	
Location Test Certificate:	2.1.2A - Required for quantities greater than 3,000 litres (aggregate water capacity).	
Tracking:	This substance is not a tracked substance.	
EPA Approval Number:	HSR002515 Aerosols (Flammable) Group Standard 2017.	
EPA Hsno Controls:	Refer to <u>www.epa.govt.nz</u> for information on Controls.	
	This substance is to be managed using the conditions specified in an applicable Group Standard.	

## Section 16 – OTHER INFORMATION

Additional information	Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.		
Abbreviations	AICS	Australian Inventory of Chemical Substances	
	ADG	Australian Code for the Transport of Dangerous Goods by Road and Rail	
	CAS	Chemical Abstract Service number	
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods	
	EPA	Environmental Protection Agency	
	GHS	Globally Harmonized System	
	IARC	International Agency for Research on Cancer	
	ΙΑΤΑ	International Air Transport Association	
	IMDG	International Maritime Dangerous Goods	
	LC <sub>50</sub>	Lethal Concentration, 50% / Median Lethal Concentration	
	LD <sub>50</sub>	Lethal Dose, 50% / Median Lethal Dose	
	LEL	Lower Explosion Limit	
	mg/m³	Milligrams per Cubic Metre	
	NZIoC	New Zealand Inventory of Chemicals	
	N.O.S.	Not otherwise specified	
	OEL	Occupational Exposure Limit	
	PEL	Permissible Exposure Limit	
	STEL	Short-Term Exposure Limit	
	STOT-RE	Specific target organ toxicity (repeated exposure)	
	STOT-SE	Specific target organ toxicity (single exposure)	
	TLV	Threshold Limit Value	
	TWA	Time Weighted Average	
	UEL	Upper Explosion Limit	

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of msds.