HYDREX TM/MC AW 32

000003000468

Version 4.1

Revision Date 2022/07/12



Print Date 2022/07/12

SECTION 1. IDENTIFICATION

Product name :	HYDREX TM/MC AW 32
Product code :	HDXAW32P5R, HDXAW32P20, HDXAW32ICT, HDXAW32IBC, HDXAW32DRR, HDXAW32DRM, HDXAW32DCT, HDXAW32, HDXAW32BLK
Manufacturer or supplier's def	
	Euromarc 203 Glover Road
	Hawera, 4610
Telephone ·	New Zealand 0800 278 600
relephone .	
Emergency telephone number	r
Emergency telephone num- : ber	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the che	mical and restrictions on use
Recommended use :	These products are designed for use as heavy duty hydraulic power transmission fluids and for lubrication where good anti- wear and anti-oxidation properties are required. They would typically be used in high-pressure hydraulic systems, machine tools, presses, compressors, pumps, gear sets, and central- ized bearing lubrication systems.
Prepared by :	Product Safety: +1 905-491-0565
	TION

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

```
IARC
```

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50, hy-	72623-87-1	70 - 90
drotreated neutral oil-based; Baseoil —		

HYDREX ^{™/MC} AW 32

000003000468

PETRO CANADA

Version 4.1

Revision Date 2022/07/12

Print Date 2022/07/12

unspecified		
Lubricating oils (petroleum), C15-30, hy- drotreated neutral oil-based; Baseoil — unspecified	72623-86-0	50 - 70
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	20 - 30
2,6-di-tert-butylphenol	128-39-2	0.1 - 1

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	 Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	 Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface

HYDREX TM/MC AW 32

000003000468

PETRO-CANADA

Version 4.1

Revision Date 2022/07/12

Print Date 2022/07/12

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	None known.
Advice on safe handling :	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage :	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum),	72623-87-1	TWA (Mist)	5 mg/m3	CA AB OEL

HYDREX ^{™/MC} AW 32

000003000468

Version 4.1

Revision Date 2022/07/12

Print Date 2022/07/12

ersion 4.1	Revision Dat	e 2022/07/12	Print D	ate 2022/07/12
C20-50, hydrotreated neutral oil-based; Baseoil — unspeci- fied				
100		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		(Mist)		
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspeci- fied	72623-86-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	Ŭ	
		late matter)		
Distillates (petroleum), hy- drotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	5 mg/m5	
		late matter)		
Engineering measures		ficient to control	ments. Good gene worker exposure f	
Personal protective equipme	nt			
Respiratory protection	ventilation is that exposure Respirator se exposure leve	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.		
Filter type	: organic vapo	ur filter		
Hand protection Material	: neoprene, nit	neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.		



HYDREX ^{™/MC} AW 32

000003000468



Version 4.1	Version 4.1		Print Date 2022/07/12
Eye protection	:	Wear face-shield and protective su problems.	it for abnormal processing
Skin and body protection	:	Choose body protection in relation tration and amount of dangerous s cific work-place.	
Protective measures	:	Wash contaminated clothing before	e re-use.
Hygiene measures	:	Remove and wash contaminated or ing the inside, before re-use. Wash face, hands and any expose handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Pale, straw-yellow.
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point Boiling point/boiling range	:	-45 °C (-49 °F) No data available
Flash point	:	206 °C (403 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8591 kg/l (15 °C / 59 °F)

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

HYDREX ^{™/MC} AW 32

000003000468

Version 4.1



Revision Date 2022/07/12

Print Date 2022/07/12

Solubility(ies)		
Water solubility	insoluble	
Partition coefficient: n- octanol/water	No data av	ailable
Viscosity Viscosity, kinematic	31.5 cSt (4	40 °C / 104 °F)
	5.5 cSt (10	00 °C / 212 °F)
Explosive properties		essurize, cut, weld, braze, solder, drill, grind or ex- ainers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, H2S, metal oxides, meth- acrylate monomers, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Eye contact Ingestion Inhalation Skin contact	of	exposure
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Assessment: The substance or mixture has no acute inhala- tion toxicity Remarks: No data available
Acute dermal toxicity	:	Assessment: The substance or mixture has no acute dermal toxicity Remarks: No data available
<u>Components:</u> Lubricating oils (petroleum) fied:), C2	20-50, hydrotreated neutral oil-based; Baseoil — unspeci-
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l
ernet: lubricants.petro-canada.com/s	sds	Page: 6

Internet: lubricants.petro-canada.com/s Trademarks are owned or used under license.

HYDREX TM/MC AW 32

000003000468



sion 4.1		Revision Date 2022/07/12	Print Date 2022/07/
		Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Lubricating oils (petroleu	m), C	15-30, hydrotreated neutral oil-ba	ısed; Baseoil — unspeci-
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,	
Acute inhalation toxicity	:	LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Distillates (petroleum), hy Acute oral toxicity		reated heavy paraffinic; Baseoil – LD50 (Rat): > 5,000 mg/kg,	- unspecified:
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
Product:			
Remarks	:	No data available	
Serious eye damage/eye i	rritat	ion	
Product:			
Remarks	:	No data available	
Respiratory or skin sensit	tisati	on	
No data available			
Germ cell mutagenicity			
No data available			
Carcinogenicity			
No data available			
Reproductive toxicity			
Reproductive toxicity			
No data available			
No data available STOT - single exposure			
	2		

HYDREX TM/MC AW 32

000003000468

Version 4.1



Print Date 2022/07/12

SECTION 12. ECOLOGICAL INFORMATION

	Ecotoxicity			
	Product: Toxicity to fish	:	Remarks: No data available	
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available	
	Toxicity to algae/aquatic plants	:	Remarks: No data available	
	Toxicity to microorganisms	:	Remarks: No data available	
	Persistence and degradabili	ty		
	Product:			
	Biodegradability	:	Remarks: No data available	
	Bioaccumulative potential No data available			
	Mobility in soil			
	No data available			
	Other adverse effects No data available			
= 1			ATIONS	-

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

HYDREX ^{™/MC} AW 32

000003000468

Version 4.1



TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:			
DSL	:	On the inventory, or in compliance with the inventory	
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.	
IECSC	:	On the inventory, or in compliance with the inventory	

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	·	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safe-
		ty, Schedule 1, Part 1: Permissible exposure values for air-
		borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

HYDREX ^{™/MC} AW 32

000003000468

Version 4.1

Revision Date 2022/07/12

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS	:	Internet: lubricants.petro-canada.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2022/07/12 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN



Print Date 2022/07/12