PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

SECTION 1. IDENTIFICATION

Product name : PURITY TM/MC FG PAG GEAR OIL 460

Product code : PFPG460P20, PFPG460DRX, PFPG460

Manufacturer or supplier's details

Euromarc

203 Glover Road Hawera, 4610 New Zealand

Telephone: 0800 278 600

Emergency telephone number

Emergency telephone num- : CHEMTREC: 1-800-424-9300;

ber Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : PURITY FG PAG Gear Oils are used for high temperature

industrial gear applications for both H1 food grade and non-H1

industrial applications.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or con-

firmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during fire-

fighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion prod: :

ucts

Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the envi-

ronment.

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Print Date 2022/08/16 Revision Date 2022/08/16

Methods and materials for containment and cleaning up Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : None known.

fire and explosion

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage

Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Personal protective equipment

Respiratory protection Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type organic vapour filter

Hand protection

Material neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

Remarks Chemical-resistant, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures Wash contaminated clothing before re-use.

Hygiene measures Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour clear

Odour mild

Odour Threshold No data available

pΗ No data available

Pour point -35 °C (-31 °F) No data available

Boiling point/boiling range

Flash point 265 °C (509 °F)

Method: Cleveland open cup

Fire Point No data available

Evaporation rate No data available

Flammability Low fire hazard. This material must be heated before ignition

will occur.

Auto-Ignition Temperature No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure No data available Relative vapour density No data available

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

Relative density : No data available

Density : 1.0768 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 460 cSt (40 °C / 104 °F)

77.3 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- :

tions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents.

Hazardous decomposition

products

May release COx, smoke and irritating vapours when heated

to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Product:

Remarks : No data available

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

Serious eye damage/eye irritation

Product:

Remarks : No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

PURITY TM/MC FG PAG GEAR OIL 460



000003009246

Version 2.2 Revision Date 2022/08/16 Print Date 2022/08/16

tem; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2022/08/16 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN