PURITY [™] FG CHAIN FLUID LIGHT



000003000411

Version 3.0

Revision Date 2022/11/21 Print Date 2022/11/21

SECTION 1. IDENTIFICATION

Product name	: PURITY ™ FG CHAIN FLUID LIGHT	

Product code : PFCHALIBC, PFCHALP20, PFCHAL, PFCHALDRX

Manufacturer or supplier's details

	Euromarc
	203 Glover Road
	Hawera, 4610
	New Zealand
:	0800 278 600
	:

Emergency telephone number

Emergency telephone	:	CHEMTREC: 1-800-424-9300;
number		Poison Control Centre: Consult local telephone directory for
		emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use :		PURITY FG Chain Fluids are food grade lubricants designed for use in a variety of applications within the food processing industry.
		NSF H1 Registered.
		All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.
Prepared by	:	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in acco	ordar	nce with the Hazardous Products Regulations
Reproductive toxicity	:	Category 2
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Suspected of damaging fertility.
Precautionary statements	:	Prevention:
		Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face

PURITY [™] FG CHAIN FLUID LIGHT



ersion 3.0	Revision Date 2022/11/21	Print Date 2022/11/2
	protection.	
	Response:	
	IF exposed or concerned: Get me	edical advice/ attention.
	Storage:	
	Store locked up.	
	Disposal:	
	Dispose of contents/ container to plant.	an approved waste disposal
Other hazards		
None known.		
IARC	No component of this product pre- or equal to 0.1% is identified as pr confirmed human carcinogen by L	robable, possible or

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	80 - 100
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	0.1 - 1

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled :	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact :	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact :	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed :	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center.



PURITY [™] FG CHAIN FLUID LIGHT



000003000411

Version 3.0		Revision Date 2022/11/21	Print Date 2022/11/21
		Never give anything by mouth to an ur Seek medical advice.	nconscious person.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.	
Notes to physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the environment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	None known.	
Advice on safe handling :	For personal protection see section 8. Smoking, eating and drinking should be prohibited in t application area.	the
ernet: lubricants.petro-canada.com/sds		Page: 3

PURITY [™] FG CHAIN FLUID LIGHT





Version 3.0	Revision Date 2022/11/21	Print Date 2022/11/21
	Use only with adequate ventilation In case of insufficient ventilation, equipment. Avoid contact with skin, eyes and Do not ingest. Keep away from heat and source Keep container closed when not i	wear suitable respiratory clothing. s of ignition.
Conditions for safe storage	 Store in original container. Containers which are opened muscle kept upright to prevent leakage. Keep in a dry, cool and well-ventil Keep in properly labelled container To maintain product quality, do not sunlight. 	lated place. ers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Engineering measures	 No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. 			
Personal protective equipment	nt			

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

PURITY [™] FG CHAIN FLUID LIGHT



000003000411

Version 3.0		Revision Date 2022/11/21	Print Date 2022/11/21
Eye protection	:	Wear face-shield and protective suit fo problems.	r abnormal processing
Skin and body protection	:	Choose body protection in relation to it concentration and amount of dangerou the specific work-place.	
Protective measures	:	Wash contaminated clothing before re	-use.
Hygiene measures	:	Remove and wash contaminated cloth including the inside, before re-use. Wash face, hands and any exposed sh handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Clear and bright
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-12 °C (10 °F)
Boiling point/boiling range	:	No data available
Flash point	:	230 °C (446 °F) Method: Cleveland open cup
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Remarks: Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available

PURITY [™] FG CHAIN FLUID LIGHT



000003000411

ersion 3.0	Revision Date 2022/11/21	Print Date 2022/11/27
Density	: 0.8622 kg/l (15 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity Viscosity, kinematic	: 151 cSt (40 °C)	
	19.8 cSt (100 °C)	
Explosive properties	: Do not pressurize, cut, weld, br expose containers to heat or so	-

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents, acids, alkalis and reducing agents.
Hazardous decomposition products	:	May release COx, NOx, SOx, POx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

information on likely routes	01 0	exposure
Eye contact Ingestion Inhalation Skin contact		
Acute toxicity		
Product:		
Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available
Components:		
White mineral oil (petroleum):	
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,

PURITY [™] FG CHAIN FLUID LIGHT



000003000411

/ersion 3.0		Revision Date 2022/11/21	Print Date 2022/11/2
76131011 3.0			
Acute inhalation toxicity	:	() 5	
		Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,	
Skin corrosion/irritation			
Product:			
Remarks	:	No data available	
Serious eye damage/eye irr	itat	ion	
Product:			
Remarks	:	No data available	
Respiratory or skin sensitis	satio	on	
No data available			
Germ cell mutagenicity			
No data available			
Carcinogenicity			
No data available			
Reproductive toxicity			
No data available			
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
ECTION 12. ECOLOGICAL INF	OR	MATION	
Ecotoxicity			
Product:			
Toxicity to fish	:	Remarks: No data available	
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available	

Toxicity to algae/aquatic	:	Remarks: No data available
plants		

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

PURITY [™] FG CHAIN FLUID LIGHT



000003000411

Version 3.0	Revision Date 2022/11/21	Print Date 2022/11/21
Biodegradability	: Remarks: No data available	
Bioaccumulative potentia No data available	I	
Mobility in soil No data available		
Other adverse effects No data available		
SECTION 13. DISPOSAL CONS	BIDERATIONS	

Disposal methods

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:					
DSL	:	On the inventory, or in compliance with the inventory			
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.			
IECSC	:	On the inventory, or in compliance with the inventory			

PURITY [™] FG CHAIN FLUID LIGHT

000003000411

Version 3.0

Print Date 2022/11/21

SECTION 16. OTHER INFORMATION

Full text of other abbreviations					
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)			
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
CA BC OEL	:	Canada. British Columbia OEL			
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
ACGIH / TWA	:	8-hour, time-weighted average			
CA AB OEL / TWA	:	8-hour Occupational exposure limit			
CA AB OEL / STEL	:	15-minute occupational exposure limit			
CA BC OEL / TWA	:	8-hour time weighted average			
CA QC OEL / TWAEV	:	Time-weighted average exposure value			
CA QC OEL / STEV	:	Short-term exposure value			

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: lubricants.petro-canada.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

PURITY [™] FG CHAIN FLUID LIGHT



000003000411

Version 3.0	Revision Date 2022/11/21	Print Date 2022/11/21
	1-800-201-6285 For Product Safety Information: 1	905-491-0565
Prepared by	: Product Safety: +1 905-491-0565	
Revision Date Date format	: 2022/11/21 : yyyy/mm/dd	

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN