PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

SECTION 1. IDENTIFICATION

Product name : PURITY ™ FG SYNTHETIC FLUID 100

Product code : PFSN100P20, PFSN100DRX, PFSN100

Manufacturer or supplier's details

Euromarc Industries Limited

203 Glover Road Hawera 4610

Telephone: 0800 278 600

Emergency telephone number

Emergency telephone : 0800 POISON - 0800 764 766;

number New Zealand National Poisons Centre. This free

emergency telephone service is available 24 hours a day, 7

days a week.

Recommended use of the chemical and restrictions on use

Recommended use : Food Grade Synthetic Vane Compressor and Vacuum Pump

Fluid.

NSF H1 Registered.

This product complies with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly

to the food product.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Suspected of damaging fertility. Suspected of damaging the

unborn child.

Precautionary statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

protection/ hearing protection.

Response:

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|-------------|-----------------------|
| Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene | 68411-46-1 | 0.1 - 1 |
| O,O,O-triphenyl phosphorothioate | 597-82-0 | 0.1 - 1 |
| reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives | 192268-65-8 | 0.1 - 1 |

^{*} Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms

and effects, both acute and

delayed

: First aider needs to protect himself.

Suspected of damaging fertility. Suspected of damaging the

unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during

firefighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

Carbon oxides (CO, CO2), nitrogen oxides (NOx), phosphorus

oxides (POx), silicon oxides (SiOx), smoke and irritating

vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : None known.

fire and explosion

Internet: www.petrocanadalubricants.com/sds
Trademarks are owned or used under license.

Page: 3 / 10

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : Colourless to light yellow.

Odour : mild

Odour Threshold : No data available

pH : No data available

Pour point : -57 °C (-71 °F)

Boiling point/boiling range : No data available

Flash point : 262 °C (504 °F)

Method: Cleveland open cup

Fire Point : No data available

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated

before ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.842 kg/l (15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Viscosity

Viscosity, kinematic : 102 cSt (40 °C)

14.3 cSt (100 °C)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, acids, alkalis and reducing

agents.

Hazardous decomposition

products

May release COx, NOx, SOx, POx, formaldehyde, smoke and

irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg,

O,O,O-triphenyl phosphorothioate:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg,

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg,

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(O,O,O-triphenyl phosphorothioate)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo :

aircraft)

UN number

IMDG-Code

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

UN 3082

964

(O,O,O-triphenyl phosphorothioate)

Class : 9
Packing group : III
Labels : 9
Ems Code

EmS Code : F-A, S-F Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(O,O,O-triphenyl phosphorothioate)

Class : 9

Internet: www.petrocanadalubricants.com/sds

Page: 8 / 10

Trademarks are owned or used under license.

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Packing group : III
Labels : 9
ERG Code : 171
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

: HSNO: HSR002605, Lubricants (Low Hazard) Group Standard 2020

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan

PURITY ™ FG SYNTHETIC FLUID 100



000003009494

Version 4.0 Revision Date 2025/03/13 Print Date 2025/03/26

Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2025/03/13 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN