SAFETY DATA SHEET	
PURITY TM/MC FG00	

000003000626

Version 2.9

Revision Date 2024/01/22



Print Date 2024/02/29

SECTION 1. IDENTIFICATION

Product name	PURITY TM/MC FG00
i iouuci name	

Product code

: PFG00KGL, PFG00P17, PFG00

Manufacturer or supplier's details

Euromarc 203 Glover Road Hawera New Zealand Telephone : 0800 278 600

Emergency telephone number

Emergency telephone	:	CHEMTREC: 1-800-424-9300;
number		Poison Control Centre: Consult local telephone directory for
		emergency number(s).

Recommended use of the c	her	nical and restrictions on use
Recommended use	:	NSF H1 Registered.
		This product complies with FDA requirements for "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.
Prepared by	:	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	30 - 100
(benzoato- O,O')hydroxy(octadecanoato- O,O')aluminium	54326-11-3	1 - 5

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

PURITY TM/MC FG00



000003000626

Version 2.9	Revision Date 2024/01/22	Print Date 2024/02/29
calcium carbonate	471-34-1	1 - 5
Polyethylene	9002-88-4	1 - 5

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

PURITY TM/MC FG00

000003000626

Version 2.9



Print Date 2024/02/29

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the environment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion	None known.
Advice on safe handling :	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage :	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL

PURITY ^{™/MC} FG00

000003000626

Version 2.9

Revision Date 2024/01/22

Print Date 2024/02/29

		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA	5 mg/m3	ACGIH
		(Inhalable particulate matter)	5 mg/m5	ACCIT
(benzoato- O,O')hydroxy(octadecanoato- O,O')aluminium	54326-11-3	TWA	10 mg/m3	CA AB OEL
		TWAEV (respirable dust)	5 mg/m3	CA QC OEL
		TWAEV	10 mg/m3	CA QC OEL
		TWA (Inhalable)	10 mg/m3	CA BC OEL
		TWA (Respirable)	3 mg/m3	CA BC OEL
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
calcium carbonate	471-34-1	TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Calcium carbonate)	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
Polyethylene	9002-88-4	TWAEV (total dust)	10 mg/m3	CA QC OEL

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection Use respiratory protection unless adequate local exhaust : ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



PURITY TM/MC FG00

000003000626



Version 2.9		Revision Date 2024/01/22	Print Date 2024/02/29
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (P\	/A), Viton [®] .
Remarks	:	Chemical-resistant, impervious gloves approved standard should be worn at chemical products if a risk assessmer necessary.	all times when handling
Eye protection	:	Wear face-shield and protective suit for problems.	or abnormal processing
Skin and body protection	:	Choose body protection in relation to i concentration and amount of dangero the specific work-place.	
Protective measures	:	Wash contaminated clothing before re	e-use.
Hygiene measures	:	Remove and wash contaminated cloth including the inside, before re-use. Wash face, hands and any exposed s handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid.
Colour	:	white
Odour	:	Bland.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-15 °C (5 °F) Base Fluid Blend
Boiling point/boiling range	:	> 371 °C (> 700 °F)
Flash point	:	249 °C (480 °F) Method: Cleveland open cup Base Fluid Blend
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Remarks: Low fire hazard. This material must be heated before ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower	:	No data available

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

PURITY TM/MC FG00

000003000626



0000000020		
Version 2.9	Revision Date 2024/01/22	Print Date 2024/02/29
flammability limit		
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.8979 kg/l (15 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity Viscosity, kinematic	: 182 cSt (40 °C) Base Fluid Blend	
	17 cSt (100 °C) Base Fluid Blend	
Explosive properties	: Do not pressurize, cut, weld, bra expose containers to heat or sou	-

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents and acids.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity

: Remarks: No data available

PURITY TM/MC FG00

000003000626



Version 2.9	Revision Date 2024/01/22	Print Date 2024/02/29
Acute inhalation toxicity	: Remarks: No data available	
Acute dermal toxicity	: Remarks: No data available	
<u>Components:</u> calcium carbonate: Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg,	
Skin corrosion/irritation		
<u>Product:</u> Remarks	: No data available	
Serious eye damage/eye ir	ritation	
Product:		
Remarks	: No data available	
Respiratory or skin sensiti	sation	
No data available		
Germ cell mutagenicity No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure No data available		
STOT - repeated exposure		
No data available		
SECTION 12. ECOLOGICAL INF	FORMATION	

Ecotoxicity

Product:		
Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available

PURITY ^{™/MC} FG00

000003000626

Version 2.9

Revision Date 2024/01/22



Print Date 2024/02/29 Persistence and degradability Product: : Remarks: No data available Biodegradability

Bioaccumulative potential

No data available

Mobility in soil No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from r	esidues :	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
		of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:		
DSL	:	On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
EINECS	:	On the inventory, or in compliance with the inventory

PURITY TM/MC FG00

000003000626



Version 2.9	Revision Date 2024/01/22 Print Date 2024/02/2	:9
AIIC	: On the inventory, or in compliance with the inventory	
IECSC	: On the inventory, or in compliance with the inventory	
ENCS	: On the inventory, or in compliance with the inventory	
NZIoC	: On the inventory, or in compliance with the inventory	
	: HSNO: HSR002605, Lubricants (Low Hazard) Group Standard 2020	

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH CA AB OEL		USA. ACGIH Threshold Limit Values (TLV) Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL		Canada. British Columbia OEL
CA QC OEL	·	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan

PURITY TM/MC FG00

000003000626



 Version 2.9
 Revision Date 2024/01/22
 Print Date 2024/02/29

 Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United

Existing Chemicals Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS	:	Internet: www.petrocanadalubricants.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-491-0565
Prepared by	:	Product Safety: +1 905-491-0565
Revision Date Date format	:	2024/01/22 yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN