PEERLESS	^{™/MC} LLG
----------	---------------------

000003001010

Version 3.0

Revision Date 2023/09/19



SECTION 1. IDENTIFICATION

Product name	:	PEERLESS TM/MC LLG
Synonyms	:	High Temperature Long Life Grease.
Product code	:	PLLLGP17, PLLLGKGL, PLLLGDRL, PLLLG, PLLLGC30
Manufacturer or supplier's d Telephone		ails Euromarc 203 Glover Road Hawera, 4610 New Zealand 0800 278 600
Emergency telephone numb	ber	
Emergency telephone num- ber	:	CHEMTREC: 1-800-424-9300; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the ch	ner	nical and restrictions on use
Recommended use	:	Peerless LLG Grease is a calcium sulphonate complex thick- ened grease designed for long life at high temperature multi- purpose automotive and industrial applications such as chas- sis, bearings and oven conveyors.
Prepared by	:	Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accord Reproductive toxicity	rdan :	ce with the Hazardous Products Regulations Category 2
GHS label elements Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Suspected of damaging fertility or the unborn child.
Precautionary statements	:	Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response: IF exposed or concerned: Get medical advice/ attention.

PETRO CANADA

PEERLESS ^{™/MC} LLG

000003001010

Version 3.0

Revision Date 2023/09/19

Print Date 2023/09/19

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C20-50,	72623-85-9	30 - < 50
hydrotreated neutral oil-based, high-		
viscosity; Baseoil — unspecified		
calcium carbonate	471-34-1	10 - < 20
reaction mass of isomers of: C7-9-	125643-61-0	5 - < 10
alkyl 3-(3,5-di-tert-butyl-4-		
hydroxyphenyl)propionate		
4,4'-methylene	10254-57-6	5 - < 10
bis(dibutyldithiocarbamate)		
Distillates (petroleum), solvent-	64742-65-0	5 - < 10
dewaxed heavy paraffinic; Baseoil —		
unspecified		
Paraffin oils (petroleum), catalytic	64742-70-7	5 - < 10
dewaxed heavy; Baseoil — unspeci-		
fied		
Benzenamine, N-phenyl-, reaction	68411-46-1	1 - < 5
products with 2,4,4-trimethylpentene		
calcium dodecylbenzenesulphonate	26264-06-2	1 - < 3
1H-Benzotriazole-1-methanamine,	94270-86-7	0.1 - < 1
N,N-bis(2-ethylhexyl)-ar-methyl-		

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing

PEERLESS TM/MC LLG

000003001010



Version 3.0		Revision Date 2023/09/19	Print Date 2023/09/19
		and shoes. Wash skin thoroughly with soap and water or use recognize skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.	
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of w for at least 15 minutes. Obtain medical attention.	rater, also under the eyelids,
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless d cian or poison control center. Never give anything by mouth to a Seek medical advice.	
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself	f.
Notes to physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), sulphur oxides (SOx), calcium oxides (CaOx), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	• :	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi-

PEERLESS TM/MC LLG

000003001010



000003001010			
Version 3.0		Revision Date 2023/09/19	Print Date 2023/09/19
Methods and materials for containment and cleaning up	:	ronment. Prevent further leakage or spillage if sa Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.	fe to do so.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist	5 mg/m3	CA QC OEL
		- Inhalable dust)		
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
calcium carbonate	471-34-1	TWAEV (to- tal dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3	CA AB OEL

PEERLESS TM/MC LLG

PETRO-CANADA

000003001010

Version 3.0

Revision Date 2023/09/19

Print Date 2023/09/19

				(Calcium car- bonate)	
			TWA (Total dust)	10 mg/m3	CA BC OEL
			TWA (respir- able dust fraction)	3 mg/m3	CA BC OEL
			STEL	20 mg/m3	CA BC OEL
Distillates (petroleum), solve dewaxed heavy paraffinic; Baseoil — unspecified	ent-	64742-65-0	TWA (Mist)	5 mg/m3	CA AB OEL
			STEL (Mist)	10 mg/m3	CA AB OEL
			TWAEV (Mist - Inhalable dust)	5 mg/m3	CA QC OEL
			TWA (Mist)	1 mg/m3	CA BC OEL
			TWA (Mist)	0.2 mg/m3	CA BC OEL
			TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Paraffin oils (petroleum), cat lytic dewaxed heavy; Baseoi — unspecified		64742-70-7	TWA (Mist)	5 mg/m3	CA AB OEL
·			STEL (Mist)	10 mg/m3	CA AB OEL
Personal protective equips Respiratory protection	ment :				
		ventilation is that exposure Respirator se exposure leve	provided or expo es are within reco election must be b	ess adequate local sure assessment of mmended exposul based on known of of the product and respirator.	demonstrates re guidelines. · anticipated
Filter type	:	ventilation is that exposure Respirator se exposure leve	provided or expo es are within reco election must be b els, the hazards o s of the selected r	sure assessment of mmended exposu based on known or of the product and	demonstrates re guidelines. · anticipated
Filter type Hand protection Material	:	ventilation is that exposure Respirator se exposure leve working limits organic vapor	provided or expo es are within reco election must be b els, the hazards o s of the selected r ur filter	sure assessment of mmended exposu based on known or of the product and	demonstrates re guidelines. anticipated the safe
Hand protection	:	ventilation is that exposure Respirator se exposure leve working limits organic vapor neoprene, nit Chemical-res approved sta	provided or expo es are within reco election must be b els, the hazards of of the selected r ur filter rile, polyvinyl alco istant, impervious ndard should be	sure assessment of mmended exposu based on known or of the product and respirator.	demonstrates re guidelines. anticipated the safe g with an then handling
Hand protection Material	:	ventilation is that exposure Respirator se exposure leve working limits organic vapor neoprene, nit Chemical-res approved sta chemical pro-	provided or expo es are within reco election must be b els, the hazards of of the selected r ur filter rile, polyvinyl alco istant, impervious ndard should be ducts if a risk ass	sure assessment of mmended exposu based on known or of the product and respirator. bhol (PVA), Viton [®] s gloves complying worn at all times w	demonstrates re guidelines. anticipated the safe , g with an when handling this is nec-
Hand protection Material Remarks	:	ventilation is that exposure Respirator se exposure leve working limits organic vapor neoprene, nit Chemical-res approved sta chemical pro- essary. Wear face-sh problems. Choose body	provided or expo es are within reco election must be b els, the hazards of of the selected r ur filter rile, polyvinyl alco istant, impervious ndard should be ducts if a risk ass ield and protectiv	sure assessment of mmended exposu based on known or of the product and respirator. bhol (PVA), Viton [®] s gloves complying worn at all times w essment indicates	demonstrates re guidelines. anticipated the safe g with an yhen handling this is nec- al processing the concen-

PEERLESS TM/MC LLG



000003001010

Version 3.0	Revision Date 2023/09/19	Print Date 2023/09/19
Hygiene measures	: Remove and wash contaminated c ing the inside, before re-use. Wash face, hands and any expose handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid.
Colour	:	Burgundy
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-15 °C (5 °F) Base Fluid Blend
Boiling point/boiling range	:	No data available
Flash point	:	256 °C (493 °F) Method: Cleveland open cup Base Fluid Blend
Fire Point	:	288 °C (550 °F) Base Fluid Blend
Evaporation rate	:	No data available
Flammability	:	Remarks: Low fire hazard. This material must be heated be- fore ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9875 kg/l (15 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available

PEERLESS TM/MC LLG

000003001010



Version 3.0	Revision Date 2023/09/19	Print Date 2023/09/19
Viscosity Viscosity, kinematic	: 100 cSt (40 °C) Base Fluid Blend	
	10.8 cSt (100 °C) Base Fluid Blend	
Explosive properties	: Do not pressurize, cut, weld, braz pose containers to heat or source	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release COx, SOx, CaOx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available
<u>Components:</u> calcium carbonate: Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg,
Distillates (petroleum), solve Acute oral toxicity		-dewaxed heavy paraffinic; Baseoil — unspecified: LD50 (Rat): > 5,000 mg/kg,
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg,

PEERLESS TM/MC LLG

000003001010

Version 3.0

Revision Date 2023/09/19



Print Date 2023/09/19

Skin corrosion/irritation

Product:

Remarks

: No data available

Serious eye damage/eye irritation

Product:

Remarks

: No data available

Respiratory or skin sensitisation

Product:

Result: Not a skin sensitizer.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradabili	ty	
Product:		
Biodegradability	:	Remarks: No data available

Bioaccumulative potential

No data available Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

PEERLESS ^{™/MC} LLG

000003001010

Version 3.0

Revision Date 2023/09/19



Print Date 2023/09/19

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions
	of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:			
DSL	:	On the inventory, or in compliance with the inventory	
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.	
IECSC	:	On the inventory, or in compliance with the inventory	

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH

: USA. ACGIH Threshold Limit Values (TLV)

PEERLESS TM/MC LLG

000003001010



Version 3.0	Revision Date 2023/09/19	Print Date 2023/09/19
CA AB OEL	: Canada. Alberta, Occupational Healt 2: OEL)	n and Safety Code (table
CA BC OEL	: Canada. British Columbia OEL	
CA QC OEL	 Québec. Regulation respecting occup ty, Schedule 1, Part 1: Permissible ex borne contaminants 	
ACGIH / TWA	: 8-hour, time-weighted average	
CA AB OEL / TWA	8-hour Occupational exposure limit	
CA AB OEL / STEL	: 15-minute occupational exposure lim	it
CA BC OEL / TWA	8-hour time weighted average	
CA BC OEL / STEL	short-term exposure limit	
CA QC OEL / TWAEV	Time-weighted average exposure val	ue

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS	: Internet: lubricants.petro-canada.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518
	Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285
	Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285
	For Product Safety Information: 1 905-491-0565

Prepared by

: Product Safety: +1 905-491-0565



PEERLESS TM/MC LLG

000003001010

Version	3.0
10131011	0.0

Revision Date 2023/09/19

Print Date 2023/09/19

Revision Date: 2023/09/19Date format: yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN