

SAFETY DATA SHEET

ENDURATEX™/MC EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

SECTION 1. IDENTIFICATION

Product name : ENDURATEX™/MC EP 320

Product code : ENT320ICT, ENT320CBE, ENT320P5R, ENT320IBC,
ENT320P20, ENT320DRX, ENT320DRR, ENT320DRM,
ENT320DCT, ENT320, ENT320BLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc.
2310 Lakeshore Road West
Mississauga ON L5J 1K2
Canada
Telephone : 1-905-403-6785

Emergency telephone number

Emergency telephone : CHEMTREC: 1-800-424-9300;
number Poison Control Centre: Consult local telephone directory for
emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : ENDURATEX EP oils are heavy duty extreme pressure gear
oils for use in enclosed industrial gear drives operating under
normal, heavy, or shock loading conditions. They are also
recommended for lubricating plain or anti-friction bearings
running under heavy or shock loading conditions.

Prepared by : Product Safety: +1 905-491-0565

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

IARC

No component of this product present at levels greater than
or equal to 0.1% is identified as probable, possible or
confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified | 64742-62-7 | 70 - 90 |
| Paraffin oils (petroleum), catalytic | 64742-70-7 | 70 - 90 |

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

| | | |
|---|------------|---------|
| dewaxed heavy; Baseoil — unspecified | | |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | 20 - 30 |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified | 72623-85-9 | 20 - 30 |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified | 72623-87-1 | 10 - 20 |

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : First aider needs to protect himself.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : No information available.
- Specific hazards during : Cool closed containers exposed to fire with water spray.

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

firefighting

Hazardous combustion products : Carbon oxides (CO, CO₂), sulphur oxides (SO_x), aldehydes, smoke and irritating vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : None known.

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labelled containers.
To maintain product quality, do not store in heat or direct sunlight.

SAFETY DATA SHEET

ENDURATEX™/MC EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|------------------------------------|---|-----------|
| Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified | 64742-62-7 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist - Inhalable dust) | 5 mg/m3 | CA QC OEL |
| | | TWA (Mist) | 1 mg/m3 | CA BC OEL |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified | 64742-70-7 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist - Inhalable dust) | 5 mg/m3 | CA QC OEL |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist - Inhalable dust) | 5 mg/m3 | CA QC OEL |
| | | TWA (Mist) | 1 mg/m3 | CA BC OEL |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil — unspecified | 72623-85-9 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist - Inhalable dust) | 5 mg/m3 | CA QC OEL |
| | | TWA (Mist) | 1 mg/m3 | CA BC OEL |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified | 72623-87-1 | TWA (Mist) | 5 mg/m3 | CA AB OEL |
| | | STEL (Mist) | 10 mg/m3 | CA AB OEL |
| | | TWAEV (Mist - Inhalable) | 5 mg/m3 | CA QC OEL |

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

| | | | | |
|--|--|---|---------|-----------|
| | | dust) | | |
| | | TWA (Mist) | 1 mg/m3 | CA BC OEL |
| | | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use.
Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : amber

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -21 °C (-6 °F)

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

| | | |
|--|---|--|
| Boiling point/boiling range | : | No data available |
| Flash point | : | 254 °C (489 °F) Method: Cleveland open cup |
| Fire Point | : | No data available |
| Evaporation rate | : | No data available |
| Flammability | : | Remarks: Low fire hazard. This material must be heated before ignition will occur. |
| Auto-Ignition Temperature | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 0.8849 kg/l (15 °C) |
| Solubility(ies) Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | No data available |
| Viscosity Viscosity, kinematic | : | 321.3 cSt (40 °C) 24.9 cSt (100 °C) |
| Explosive properties | : | Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Possibility of hazardous reactions | : | Hazardous polymerisation does not occur. Stable under normal conditions. |
| Conditions to avoid | : | No data available |
| Incompatible materials | : | Reactive with oxidising agents. |
| Hazardous decomposition products | : | May release CO _x , NO _x , SO _x , PO _x , H ₂ S, hydrocarbons, methacrylate monomers, asphyxiants, smoke and irritating vapours when heated to decomposition. |

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No data available

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No data available

Components:

Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg,

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity;

Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks : No data available

Serious eye damage/eye irritation

Product:

Remarks : No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified :

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l
Exposure time: 72 h

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labelled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

SAFETY DATA SHEET

ENDURATEX™/MC EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

TSCA Inventory or are in compliance with a TSCA Inventory exemption.

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

| | |
|--------------------|---|
| ACGIH | : USA. ACGIH Threshold Limit Values (TLV) |
| CA AB OEL | : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL) |
| CA BC OEL | : Canada. British Columbia OEL |
| CA QC OEL | : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants |
| ACGIH / TWA | : 8-hour, time-weighted average |
| CA AB OEL / TWA | : 8-hour Occupational exposure limit |
| CA AB OEL / STEL | : 15-minute occupational exposure limit |
| CA BC OEL / TWA | : 8-hour time weighted average |
| CA QC OEL / TWA EV | : Time-weighted average exposure value |

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

SAFETY DATA SHEET

ENDURATEX^{TM/MC} EP 320

000003000429



Version 4.1

Revision Date 2024/01/10

Print Date 2024/05/21

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds
Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518
Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285
Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2024/01/10
Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN