

000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

SECTION 1. IDENTIFICATION

Product name PURITY TM/MC FG SPRAY

Product code : PFMUB12, PFMU

Manufacturer or supplier's details

Euromarc Industries Limited

203 Glover Road Hawera 4610

Telephone: 0800 278 600

Emergency telephone number

Emergency telephone : 0800 POISON - 0800 764 766

number

New Zealand National Poisons Centre. This free emergency telephone service is available 24 hours a day, 7 days a week.

Recommended use of the chemical and restrictions on use

Recommended use Purity FG Spray is an advanced multipurpose food grade

lubricant in an aerosol can.

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be

added directly to the food product.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable aerosols Category 1

Gases under pressure Liquefied gas

Reproductive toxicity Category 2

Simple Asphyxiant Category 1

GHS label elements

Hazard pictograms







Signal word Danger

Hazard statements Extremely flammable aerosol.

> Contains gas under pressure; may explode if heated. Suspected of damaging fertility or the unborn child.



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

May displace oxygen and cause rapid suffocation.

Precautionary statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response:

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	60 - 70
propane	74-98-6	10 - 20
isobutane	75-28-5	5 - 10
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	0.1 - 0.25

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush eyes or skin with plenty

of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

First aider needs to protect himself.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Carbon dioxide (CO2) Alcohol-resistant foam

Water spray Water fog

Unsuitable extinguishing

media

Do NOT use water jet.

Specific hazards during

firefighting

If the product release cannot be shut off safely, allow the

product to burn itself out.

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur

oxides (SOx), phosphorus oxides (POx), carbonyl halides, smoke and irritating vapours as products of incomplete

combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus and full protective

wear.

Wear a positive-pressure supplied-air respirator with full

facepiece.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition.

Mark the contaminated area with signs and prevent access to



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Use explosion-proof ventilation equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13). Remove all sources of ignition. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Keep away from heat and sources of ignition.

Advice on safe handling : For personal protection see section 8.

Use only with adequate ventilation.

Smoking, eating and drinking should be prohibited in the

application area.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Do not breathe vapours or spray mist. Use explosion-proof equipment. Wear suitable protective equipment.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist	5 mg/m3	CA QC OEL
		- Inhalable		
		dust)		
		TWA (Mist)	1 mg/m3	CA BC OEL



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH

Engineering measures : Adequate ventilation to ensure that Occupational Exposure

Limits are not exceeded.

Use explosion-proof ventilation equipment.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile. Consult your PPE provider for breakthrough

times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get

permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of

hardening and cracks, they should be changed.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Colour : Purity FG Lubricant is clear and bright.

Odour : Hydrocarbon or petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : $-12 \,^{\circ}\text{C} \, (10 \,^{\circ}\text{F})$

Purity FG Lubricant:

Boiling point : No data available

Flash point : -156 °C (-249 °F)

Propellant:

Fire Point : No data available

Evaporation rate : No data available

Flammability : Extremely flammable aerosol.

Remarks: Propellant is a flammable gas., Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable

distance to sources of ignition and flash back.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper

flammability limit

9.5 %(V) Propellant:

Lower explosion limit / Lower

flammability limit

1.8 %(V) Propellant:

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.862 kg/l (15 °C)

Purity FG Lubricant:

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, kinematic : 150 cSt (40 °C)

Purity FG Lubricant:

19.8 cSt (100 °C) Purity FG Lubricant:



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition. Container explosion may occur under fire conditions or when heated.

Ruptured cylinders may rocket.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Reactive with oxidising agents, reducing agents, acids, alkalis,

liquid oxygen and alkali metals and their hydroxides.

Hazardous decomposition

products

May release COx, NOx, SOx, POx, carbonyl halides, smoke

and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658,000 mg/m3

Exposure time: 4 h
Test atmosphere: gas



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Skin corrosion/irritation

Product:

No data available Remarks

Serious eye damage/eye irritation

Product:

Remarks No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

aquatic invertebrates

Toxicity to daphnia and other : Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms Remarks: No data available

Persistence and degradability

Product:

: Remarks: No data available Biodegradability

Bioaccumulative potential

No data available

SAFETY DATA SHEET

PURITY TM/MC FG SPRAY



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.

Packing group : Not assigned by regulation

Labels : Flammable Gas

Packing instruction (cargo : 2

aircraft)

IMDG-Code

UN number : UN 1950

Proper shipping name : AEROSOLS LIMITED QUANTITY

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG

UN number : UN 1950

Proper shipping name : AEROSOLS LIMITED QUANTITY

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

Internet: www.petrocanadalubricants.com/sds

Page: 9 / 11 Petro-Canada Lubricants is a HF Sinclair brand

PETRO CANADA

000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EINECS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

: HSNO: HSR002605, Lubricants (Low Hazard) Group

Standard 2020

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and

safety, Schedule 1, Part 1: Permissible exposure values for

airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing

SAFETY DATA SHEET

PURITY TM/MC FG SPRAY



000003010624

Version 2.0 Revision Date 2024/01/02 Print Date 2024/01/02

Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2024/01/02 Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN