according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PURITY ™ FG AW HYDRAULIC FLUID 32

Product code : PFAW32P20, PFAW32IBC, PFAW32, PFAW32DRX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : PURITY FG AW Hydraulic Fluids are food grade hydraulic

Substance/Mixture fluids and light gear oils.

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570

"Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be

added directly to the food product.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Euromarc Industries Limited

203 Glover Road Hawera 4610

Telephone : 0800 278 600

1.4 Emergency telephone number

Emergency telephone

number

: 0800 POISON - 0800 764 766

New Zealand National Poisons Centre. This free emergency telephone service is available 24 hours a day, 7 days a week.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Hazard statements : H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27- 0010	Asp. Tox. 1; H304	90 - 100
O,O,O-triphenyl phosphorothioate	597-82-0 209-909-9 01-2119979545-21	Aquatic Chronic 1; H410	0.25 - 1
	0. 2.1.007.00.10 2.	M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1 270-128-1 01-2119491299-23	Aquatic Chronic 3; H412 Repr. 2; H361f	0.25 - 1
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119480433-40- 0000	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.25 - 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), silicon oxides (SiOx), smoke and

irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions Do not allow uncontrolled discharge of product into the

environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Prevent further leakage or spillage if safe to do so.

> Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

Internet: www.petrocanadalubricants.com/sds

Page: 4 / 15

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against :

fire and explosion

None known.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use. Wash face, hands and any

exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information see Section 1 of the safety data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

8-hour TLV-TWA of 5 mg/m³ recommended by manufacturer based on ACGIH TLV for mineral oil mists. Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : viscous liquid

Colour : colourless

Odour : Mild petroleum oil like.

Odour Threshold : No data available

Pour point : -18 °C

Boiling point/boiling range : No data available

Flash point : 225 °C

Method: Cleveland open cup

pH : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

Fire Point : No data available

Auto-Ignition Temperature : No data available

Evaporation rate : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8629 kg/l (15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 29.8 cSt (40 °C)

5.2 cSt (100 °C)

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

9.2 Other information

Particle size : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, acids and alkalis.

10.6 Hazardous decomposition products

Hazardous decomposition

May release COx, NOx, SOx, POx, formaldehyde, smoke and

irritating vapours when heated to decomposition.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

products

Eye contact Ingestion

> Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

O,O,O-triphenyl phosphorothioate:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): 6,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Product:

Remarks : All components listed in Annex VI to which Note L applies,

and contained in the product, have been shown to contain less than 3% DMSO extractables as measured by IP346.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 9 / 15 Petro-Canada Lubricants is a HF Sinclair brand

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components

> considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Remarks: No data available Toxicity to fish

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

White mineral oil (petroleum):

Toxicity to fish NOEC (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

plants

NOEC (algae): > 100 mg/l

Exposure time: 72 h

O,O,O-triphenyl phosphorothioate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic Internet: www.petrocanadalubricants.com/sds

Trademarks are owned or used under license.

Page: 10 / 15 Petro-Canada Lubricants is a HF Sinclair brand

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY [™] FG AW HYDRAULIC FLUID 32

000003000529

Revision Date 2025/03/13 Version 5.0 Print Date 2025/03/20

toxicity)

Toxicity to fish (Chronic

toxicity)

: NOEC: 0.0017 mg/l

Exposure time: 97 d

Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic

toxicity)

10

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

2,6-di-tert-butyl-p-cresol:

Toxicity to fish LC50 (Danio rerio (zebra fish)): > 0.57 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 0.48 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (green algae): > 0.4 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

Product:

: Remarks: No data available Biodegradability

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

This substance/mixture contains components considered to Assessment

be either persistent, bioaccumulative and toxic (PBT), or very

persistent and very bioaccumulative (vPvB).

Components:

O,O,O-triphenyl phosphorothioate:

Assessment : PBT substance

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14: Transport information

14.1 UN number or ID number

IMDG : UN 3082 IATA (Cargo) : UN 3082

14.2 UN proper shipping name

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(O,O,O-triphenyl phosphorothioate)

IATA (Cargo) : Environmentally hazardous substance, liquid, n.o.s.

(O,O,O-triphenyl phosphorothioate)

14.3 Transport hazard class(es)

Class Subsidiary risks

IMDG : 9 **IATA (Cargo)** : 9

14.4 Packing group

IMDG

Packing group : III Labels : 9

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 12 / 15 Petro-Canada Lubricants is a HF Sinclair brand

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

964

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : ADR: UN3082, ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (O,O,O-triphenyl

phosphorothioate), 9, PGIII

ADN: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (O,O,O-triphenyl

phosphorothioate), 9, PGIII

RID: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (O,O,O-triphenyl

phosphorothioate), 9, PGIII

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High : Not applicable

Concern for Authorisation (Article 59).

Regulation (EU) No 2024/590 on substances that : Not applicable

deplete the ozone layer

Regulation (EU) 2019/1021 on persistent organic : Not applicable

pollutants (recast)

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Water hazard class : WGK 2 obviously hazardous to water

(Germany)

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 13 / 15
Petro-Canada Lubricants is a HF Sinclair brand

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

HSNO: HSR002605, Lubricants (Low Hazard) Group

Standard 2020

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Repr. : Reproductive toxicity

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 14 / 15 Petro-Canada Lubricants is a HF Sinclair brand

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PURITY ™ FG AW HYDRAULIC FLUID 32

000003000529

Version 5.0 Revision Date 2025/03/13 Print Date 2025/03/20

population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

Order Email for packed goods: pcepackage@hfsinclair.com

Order Email for bulk: pceorders@hfsinclair.com Telephone: +31 88313 0365 / +31 88313 0366 For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Classification of the mixture: Classification procedure:

Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG EU/EN