SAFETY DATA SHEET		
PURITY <sup>™/MC</sup> FG2		PETRO-CANADA
000003001373		
Version 2.9	Revision Date 2024/01/22	Print Date 2024/01/22
SECTION 1. IDENTIFICATION		
Product name :	PURITY TMMC FG2	
Product code :	PFG2AL2, PFG2AL1, PFG2P17, PFG PFG2, PFG2C30	2KGL, PFG2DRL,
Manufacturer or supplier's det	<b>ails</b> Euromarc Industries Limited 203 Glover Road Hawera 4610 New Zealand	
Telephone :	0800 278 600	
Emergency telephone number		
Emergency telephone num- : ber	0800 278 600 Monday to Friday 7am to 5pm.	
Recommended use of the cher	nical and restrictions on use	
Recommended use :	NSF H1 Registered.	
	This product complies with FDA requir with Incidental Food Contact". It is inte industrial and food equipment. It shou to the food product.	ended for application on

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	30 - 100
calcium carbonate	471-34-1	1 - 5
Polyethylene	9002-88-4	1 - 5



PURITY TM/MC FG2

### 000003001373

Version 2.9



Print Date 2024/01/22

 $^{\ast}$  Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASUR	RES	
If inhaled	:	Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice. In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	First aider needs to protect himself.
Notes to physician	:	Treat symptomatically.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	:	No information available.
Specific hazards during fire- fighting	:	Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	:	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), smoke and irritating vapours as products of incomplete combustion.
Further information	:	Prevent fire extinguishing water from contaminating surface water or the ground water system.

# PURITY TM/MC FG2

### 000003001373

Version 2.9



Print Date 2024/01/22

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Environmental precautions :	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for : containment and cleaning up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use.
Conditions for safe storage	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun- light.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist	5 mg/m3	CA QC OEL

# PURITY <sup>™/MC</sup> FG2

## 000003001373

Version 2.9

Print Date 2024/01/22

		- Inhalable			
		dust)	1 m a/m 2	CA BC OEL	
		TWA (Mist)	1 mg/m3		
		TWA (Inhal-	5 mg/m3	ACGIH	
		able particu-			
	474.04	late matter)	10		
calcium carbonate	471-34-	```	10 mg/m3	CA QC OEL	
		tal dust)			
		TWA	10 mg/m3	CA AB OEL	
			(Calcium car-		
			bonate)		
		TWA (Total	10 mg/m3	CA BC OEL	
		dust)			
		TWA (respir-	3 mg/m3	CA BC OEL	
		able dust			
		fraction)			
		STEL	20 mg/m3	CA BC OEL	
Polyethylene	9002-88	3-4 TWAEV (to-	10 mg/m3	CA QC OEL	
		tal dust)			
Engineering measures		cial ventilation require be sufficient to contro inants.			
Personal protective equip	nent				
	that ex Respira exposu	rentilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.			
Filter type	: organic	vapour filter			
Hand protection					
Material	: neopre	ne, nitrile, polyvinyl al	cohol (PVA), Viton®	)	
Remarks	approv	cal-resistant, imperviou ed standard should be al products if a risk as	e worn at all times w	when handling	
Eye protection	: Wear fa probler	ace-shield and protect ns.	ive suit for abnorma	al processing	
Skin and body protection	tration	e body protection in re and amount of danger ork-place.			
Protective measures	: Wash o	contaminated clothing	before re-use.		
Hygiene measures	ing the	e and wash contamina inside, before re-use. ace, hands and any e g.			



# PURITY TM/MC FG2

### 000003001373

Version 2.9



Print Date 2024/01/22

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Semi-solid.
Colour	:	Cream-white
Odour	:	Bland.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-15 °C (5 °F) Base Fluid Blend
Boiling point/boiling range	:	No data available
Flash point	:	249 °C (480 °F) Method: Cleveland open cup Base Fluid Blend
Fire Point	:	No data available
Evaporation rate	:	No data available
Flammability	:	Remarks: Low fire hazard. This material must be heated be- fore ignition will occur.
Auto-Ignition Temperature	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9150 kg/l (15 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity Viscosity, kinematic	:	182 cSt ( 40 °C) Base Fluid Blend
		17 cSt ( 100 °C) Base Fluid Blend

PURITY TM/MC FG2

## 000003001373



000003001373			
Version 2.9		Revision Date 2024/01/22	Print Date 2024/01/22
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or pose containers to heat or sources of ignition.	
SECTION 10. STABILITY AND RE	AC	ΤΙVΙΤΥ	
Reactivity	:	No dangerous reaction known under	conditions of normal use.
Chemical stability	:	Stable under normal conditions.	
Possibility of hazardous reac- tions	:	Hazardous polymerisation does not o Stable under normal conditions.	ccur.
Conditions to avoid	:	No data available	
Incompatible materials	:	Reactive with oxidising agents.	

to decomposition.

: May release COx, smoke and irritating vapours when heated

# SECTION 11. TOXICOLOGICAL INFORMATION

Hazardous decomposition

products

#### Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact		
Acute toxicity		
Product: Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available
Components: calcium carbonate: Acute oral toxicity Skin corrosion/irritation	:	LD50 (Rat): > 2,000 mg/kg,
<u>Product:</u> Remarks	:	No data available
Serious eye damage/eye irr	itat	ion
<u>Product:</u> Remarks	:	No data available
Respiratory or skin sensitis	atio	on

No data available Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

# PURITY TM/MC FG2

#### 000003001373

Version 2.9



Print Date 2024/01/22

#### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

#### **Reproductive toxicity**

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Persistence and degradability	ty	
Product:		
Biodegradability	:	Remarks: No data available
Biodegradability Bioaccumulative potential	:	Remarks: No data available
	:	Remarks: No data available
Bioaccumulative potential	:	Remarks: No data available

# Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed dis- posal company. Waste must be classified and labelled prior to recycling or disposal.
---------------------	---	---

# PURITY TM/MC FG2

### 000003001373

Version 2.9

Revision Date 2024/01/22

Print Date 2024/01/22

Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### **National Regulations**

**TDG** Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:				
DSL	:	On the inventory, or in compliance with the inventory		
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.		
EINECS	:	On the inventory, or in compliance with the inventory		
IECSC	:	On the inventory, or in compliance with the inventory		
AIIC	:	On the inventory, or in compliance with the inventory		
ENCS	:	On the inventory, or in compliance with the inventory		
NZIoC	:	On the inventory, or in compliance with the inventory		
	:	HSNO: HSR002605, Lubricants (Low Hazard) Group Stand- ard 2020		

#### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table
	2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safe-
	ty, Schedule 1, Part 1: Permissible exposure values for air-

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.



### PURITY <sup>™/MC</sup> FG2

#### 000003001373

Version 2.9



Print Date 2024/01/22

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS	<ul> <li>Internet: www.petrocanadalubricants.com/sds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518 Ontario &amp; Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285 Quebec &amp; Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-491-0565</li> </ul>
Prepared by	: Product Safety: +1 905-491-0565
Revision Date	: 2024/01/22

Date format : yyyy/mm/dd

PURITY TM/MC FG2

#### 000003001373

Version 2.9

#### Revision Date 2024/01/22

t act automative, and will be used only as a guide

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN



Print Date 2024/01/22